

---

## **GPS + Glonass Puck Antenna**

---

- **High Efficiency LNA**
- **GPS + Glonass Antenna**
- **Outdoor use**
- **Center Bolt mount**

ADA-A101-S is designed for GPS and Glonass navigational applications, where outside mounting is preferred. The antenna has a small foot print and can withstand high winds and wet environment.



**RoHS**

## Specification

Antenna	Specification
Frequency	1575.42 $\pm$ 10MHz +1602MHz $\pm$ 8MHz
Patch Dimension	25mm x 25mm x 4mm
Gain	+1.0 dBic typ, Ref to 70 x70mm ground plane
Polarazation	RHCP
Axel Ratio	3.0dB Max, Ref. to 70 x70mm Graound Plane
	LNA
Frequency Range	1575.42 $\pm$ 10MHz; 1602MHz $\pm$ 8MHz
Gain	1575.42MHz, 26dBic Typ. 1602MHz, 26dBic Typ.
Noise Figure	1.5dBic Typ. 2.6dBic Max @ 25°C $\pm$ 5°C @3.0VDC
Output Impedance	50 $\Omega$
Output VSWR	2.0 Max
Out of Band Rejection	1587.5MHz $\pm$ 140MHz, 15dB Min
	Total Specification
Frequency Range	1575.42 $\pm$ 10MHz +1602MHz $\pm$ 8MHz
Gain	29dBic $\pm$ 3dBic
Output Impedance	50 $\Omega$
VSWR	2.0 Max
	Electrical Specification
Operating Voltage	Min: 2.5 V Typ: 3.0 V Max:5.5 V
Current Consumption	Typ: 13 mA Max: 18mA @ 5.0V
	Environmental Cond.
Operating Temperature	-40°C to + 85°C
Storage Temperture	-40°C to + 85°C
Relative Humidity	40% to 95%

	Mechanical Specification
RF Cable	Standard 3 m RG174/U with standard connector
RF Connector	SMA
Antenna Size	Ø52mm x 24mm, Bolt Ø12mm x 20mm
Weight	60g + Cable.
Mounting	Center Bolt
Water proof	Under Water 50cm, 30min max
Shock	10 msec. Half Sine Wave
Vibration	10~200Hz Log. Sweep 3.0G sweep time: 15 Minutes, 3 Axes
Cable Pulling Off Force	Min 7kg/10sec, no visible damage.
Bending Test	Min 90 Degree left and right 1000 cycles, no damage.

## Ordering codes

TYPE	Description	Comment
ADA-A101-C	GPS + Glonass Puck Antenna	Center Bolt Puck Antenna

For the latest updates, visit our Web site: [www.adactus.se](http://www.adactus.se)

### **Disclaimer**

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein.

This publication supersedes and replaces all information previously supplied. Adactus products are not authorised as critical components in life support devices or systems.